

SC-132A/ SC-008A (option)

(Speaker Line Checker)


[ZOOM](#)
[PRINT](#)

■ Features

- Speaker Line Under Load Check
- Speaker Line Open Check.
- Watch dog function
- Speaker Line Impedance Check.
- Speaker Line Short Check.
- Automatical check in adjustable time intervals between 1 minutes and 24 hours.
- Interruption of the check when emergency announcement comes up
- Store by No volatile memory(EE-PROM).
- AC and DC (24v) operation.
- Buzzer Sound on/off function.
- Alert sound and LED indicator when speaker line fault.
- Permissible speaker line check 100V/70V.
- Bridging of the existing volume control with the intergrated relay during the check.
- Speaker Line Over Load Check
- Max. 32 Speaker Lines(with 4 Relay Board).
- Ground Fault detection

■ Technical specifications

Check range	20~1600Ω
Check time	Less than 100m sec / Channel
Signal input	32 Channel(with 4 relay board)
Signal output	32 Channel(with 4 relay board)
ADC resolution	10Bit(1024 step)
Power consumption	24W
Power (option)	120~240V AC, 50/60Hz , 24V DC
Dimensions (mm/ inch)	483(W) x 44(H) x 200(D)
	19(W) x 1.7(H) x 7.9(D)
Weight (kg)	3.1kg

[LIST](#)