

6W



Technical data	HWR103T	HWR103T-A (with control)
Load rating	6 W	6 W
Transformer tapings	6 W (100V)	6-3-1.5-0.75 W (70.7V) 6-3-1.5 W (100V)
Frequency range	150-15KHz	150-15KHz
SPL(@1W/m)	90dB	90dB
Speaker Ø and Impedance	5" / 8 ohms	5" / 8 ohms
Dimension HxWxD(mm)	193x175x85mm	194x188x87mm
Material,Colour	ABS , white	ABS , white

6W



Technical data	HWR127T
Load rating at 100V	6 W
Transformer tapings	6-3-1.5W (100V)
Frequency range	150-16KHz
SPL(@1W/m)	90dB
Speaker Ø and Impedance	5" / 8 ohms
Dimension HxWxD(mm)	184x190x85mm
Material,Colour	ABS,white

10W



Technical data	HWR110T
Load rating at 100V	10 W
Frequency range	150-15KHz
SPL(@1W/m)	90dB
Speaker Ø and Impedance	5" / 8 ohms
Dimension HxWxD(mm)	180x140x70mm
Material,Colour	ABS , white

3W



Technical data	HWR111T
Load rating at 100V	3 W
Frequency range	200-15KHz
SPL(@1W/m)	88dB
Speaker Ø and Impedance	3" / 8 ohms
Dimension HxWxD(mm)	120x120x58mm
Material,Colour	ABS , white