

TA-1060/1120

Mixing Amplifier



FEATURES

- Pre-Amp out / Amp-in for extensions to power amplifiers.
- Individual gain control for channel 1-5.
- 4 mic input+4line inputs two/four tone Chime, 2 siren tones.
- Voice priority for Mic 1.
- Telephone Input & Music On Hold (tuner only).
- Optional modules (TP-100, DM-100, CDP-100M, CDR-100RDS, TP-100RDS).
- Bass / treble tone control.
- 4 speaker outputs.
- Remote Chime with external terminal.
- Individual 4 Zone speaker selector .
- VU output meter.
- 100V / 70V output selector.
- AC / DC 24V.
- Bass & treble control for pack series.

TECHNICAL SPECIFICATIONS

TECHNICAL DATA	TA-1060	TA-1120
THD at 1KHz	Less than 1%	Less than 1%
Rated output(at 1% THD)	60W(RMS)/90W(MAX)	120W(RMS)/180W(MAX)
Power consumption	145W	295W
Frequency response(±3dB)	80Hz to 15kHz	
Equalizer	Bass : ±10dB at 100Hz,Treble : ±10dB at 10kHz	
Signal to noise ratio	Line : More than 70dB, MIC : More than 60dB	
Input	MIC 1~4 : 3mV, LINE : 300mVPHONE : 2.4mV	
Power	AC230V/50Hz, DC24V	
Dimensions m/m	420(W) x 110(H) x 320(D) m/m	
Weight(kg)	10.5kg	12.5kg

RMK-100 (Option)

Rack Mounting Bracket For TA-1060/1120



MODULE SERIES (Option)

CDP-100M

CD & Player



CDR-100RDS

CD & Receiver



TP-100

FM/AM Tuner



DM-100

Digital Message



TP-100RDS

Digital RDS Tuner



DRAWING

